### **Troodon OBD**

## Connecting to a phone using Bluetooth

### **Troodon OBD**

# Connecting to a phone using Bluetooth

### 1. Download and install the Troodon OBD app to your phone.

The application is available on App Store and Google Play. The test version is available upon request via email at diagnostika@devcom.cz.

### 2. Connect the interface to the vehicle.

Connect the interface to the vehicle using the OBD connector. Initialization process takes approximately 40 seconds. The right indicator on the interface will light up first and then start blinking. Subsequently, the left indicator on the device will also illuminate. This indicates that the interface is ready.



### 1. Download and install the Troodon OBD app to your phone.

The application is available on App Store and Google Play. The test version is available upon request via email at diagnostika@devcom.cz.

### Connect the interface to the vehicle.

Connect the interface to the vehicle using the OBD connector. Initialization process takes approximately 40 seconds. The right indicator on the interface will light up first and then start blinking. Subsequently, the left indicator on the device will also illuminate. This indicates that the interface is ready.



### 3. Launch the Troodon OBD app.

Turn on Bluetooth and launch the downloaded Troodon OBD app.

### 3. Launch the Troodon OBD app.

Turn on Bluetooth and launch the downloaded Troodon OBD app.








### 4. Access to location and storage

To connect to the device, the application requires permission to discover devices in the vicinity and determine their relative positions. The reason for this requirement is the utilization of Bluetooth LE technology for device connectivity.


Furthermore, the application may require access to your phone's storage for certain activities, primarily for the purpose of storing and reading logs and other auxiliary data.



### 4. Access to location and storage

To connect to the device, the application requires permission to discover devices in the vicinity and determine their relative positions. The reason for this requirement is the utilization of Bluetooth LE technology for device connectivity.

Furthermore, the application may require access to your phone's storage for certain activities, primarily for the purpose of storing and reading logs and other auxiliary data.



# Searching Searching Connect to device Connect the interface to the vehicle using the OBD connect roand observe the light signal. Select device from the list. More information Device list Troodon-TEST51009 Preferred language: EN Connection problems?

# 5. In the Troodon OBD application, connect to the device.

The Troodon OBD application automatically searches for available diagnostic interfaces upon startup. Locate your device in the list and select it.

If the device is not displayed, please check the Bluetooth settings on your phone and ensure that location access permissions are granted. Then, disconnect and reconnect the interface and restart the application.



# 5. In the Troodon OBD application, connect to the device.

The Troodon OBD application automatically searches for available diagnostic interfaces upon startup. Locate your device in the list and select it.

If the device is not displayed, please check the Bluetooth settings on your phone and ensure that location access permissions are granted. Then, disconnect and reconnect the interface and restart the application.

### 6. Establish connection with the vehicle

After connecting to the device, you can initiate a diagnostic connection with the vehicle. Continue by selecting the brand, model, and control unit, following the on-screen instructions.

### 6. Establish connection with the vehicle

After connecting to the device, you can initiate a diagnostic connection with the vehicle. Continue by selecting the brand, model, and control unit, following the on-screen instructions.



